



SPECIFICATIONS

	MAX LOAD	DIM "A" COLLAPSED	DIM "A" EXTENDED	STROKE	OIL CAPACITY	WEIGHT
HCL5002	5114 KN/ 575 TON	357 [14.06]	407 [16.02]	50 [1.97]	3,653 CM ³ [222.92 IN ³]	341 KG [751 LBS]
HCL5004		407 [16.02]	507 [19.96]	100 [3.94]	7,306 CM ³ [445.85 IN ³]	390 KG [860 LBS]
HCL5006		457 [17.99]	607 [23.90]	150 [5.91]	10,959 CM ³ [668.77 IN ³]	439 KG [968 LBS]
HCL5008		507 [19.96]	707 [27.83]	200 [7.87]	14,612 CM ³ [891.70 IN ³]	489 KG [1077 LBS]
HCL50010		557 [21.93]	807 [31.77]	250 [9.84]	18,265 CM ³ [1114.62 IN ³]	538 KG [1186 LBS]
HCL50012		607 [23.90]	907 [35.71]	300 [11.81]	21,918 CM ³ [1337.55 IN ³]	587 KG [1294 LBS]
MAX PRESSURE - 700 BAR/10,150 PSI						

Language Code - Primary/Secondary eng/	Document Type: ID DRAWING	Description: ID SPEC HCL500			
THIRD ANGLE PROJECTION	Technical Reference: Juan Carlos Gomez	Rev A	Date of Issue 2016DEC12	HCL500ID	Sheet 1/1
DO NOT SCALE DRAWING	Approver: Steve Held				
Per ASME Y14.5 - 2009	Creator: John Van Roy	ENERPAC			