



SPECIFICATIONS

	MAX LOAD	DIM "A" COLLAPSED	DIM "A" EXTENDED	STROKE	OIL CAPACITY	WEIGHT
HCL6002	5987 KN/ 673 TON	380 [14.96]	430 [16.93]	50 [1.97]	4,276 CM ³ [260.97 IN ³]	427 KG [942 LBS]
HCL6004		430 [16.93]	530 [20.87]	100 [3.94]	8,553 CM ³ [521.94 IN ³]	484 KG [1067 LBS]
HCL6006		480 [18.90]	630 [24.80]	150 [5.91]	12,829 CM ³ [782.90 IN ³]	541 KG [1193 LBS]
HCL6008		530 [20.87]	730 [28.74]	200 [7.87]	17,106 CM ³ [1043.87 IN ³]	598 KG [1319 LBS]
HCL60010		580 [22.83]	830 [32.68]	250 [9.84]	21,382 CM ³ [1304.84 IN ³]	655 KG [1444 LBS]
HCL60012		630 [24.80]	930 [36.61]	300 [11.81]	25,659 CM ³ [1565.81 IN ³]	712 KG [1570 LBS]
MAX PRESSURE - 700 BAR/10,150 PSI						

Language Code - Primary/Secondary eng/	Document Type: ID DRAWING	Description: ID SPEC HCL600		
THIRD ANGLE PROJECTION	Technical Reference: Juan Carlos Gomez	Rev A	Date of Issue 2016DEC12	Sheet 1/1
DO NOT SCALE DRAWING	Approver: Steve Held	HCL600ID		
Per ASME Y14.5 - 2009	Creator: John Van Roy	ENERPAC		