



### SPECIFICATIONS

	MAX LOAD	DIM "A" COLLAPSED	DIM "A" EXTENDED	STROKE	OIL CAPACITY	WEIGHT
HCL8002	8149 KN/ 916 TON	430 [16.93]	480 [18.90]	50 [1.97]	5,821 CM <sup>3</sup> [355.21 IN <sup>3</sup> ]	668 KG [1472 LBS]
HCL8004		480 [18.90]	580 [22.83]	100 [3.94]	11,642 CM <sup>3</sup> [710.41 IN <sup>3</sup> ]	746 KG [1646 LBS]
HCL8006		530 [20.87]	680 [26.77]	150 [5.91]	17,462 CM <sup>3</sup> [1065.62 IN <sup>3</sup> ]	825 KG [1819 LBS]
HCL8008		580 [22.83]	780 [30.71]	200 [7.87]	23,283 CM <sup>3</sup> [1420.82 IN <sup>3</sup> ]	904 KG [1992 LBS]
HCL80010		630 [24.80]	880 [34.65]	250 [9.84]	29,104 CM <sup>3</sup> [1776.03 IN <sup>3</sup> ]	982 KG [2166 LBS]
HCL80012		680 [26.77]	980 [38.58]	300 [11.81]	34,925 CM <sup>3</sup> [2131.24 IN <sup>3</sup> ]	1061 KG [2339 LBS]

MAX PRESSURE - 700 BAR/10,150 PSI

Language Code - Primary/Secondary eng/	Document Type: ID DRAWING	Description: ID SPEC HCL800		
<b>THIRD ANGLE PROJECTION</b>	Technical Reference: Juan Carlos Gomez	Rev A	Date of Issue 2016DEC12	Sheet 1/1
DO NOT SCALE DRAWING	Approver: Steve Held	HCL800ID		
Per ASME Y14.5 - 2009	Creator: John Van Roy			