



SPECIFICATIONS

	MAX LOAD	DIM "A" COLLAPSED	DIM "A" EXTENDED	DIM "B"	STROKE	OIL CAPACITY	WEIGHT
HCR502	550 KN/ 62 TON	183 [7.20]	233 [9.17]	45 [1.77]	50 [1.97]	393 CM ³ [23.96 IN ³]	17 KG [37 LBS]
HCR504		233 [9.17]	333 [13.11]		100 [3.94]	785 CM ³ [47.93 IN ³]	21 KG [46 LBS]
HCR506		283 [11.14]	433 [17.05]		150 [5.91]	1,178 CM ³ [71.89 IN ³]	25 KG [54 LBS]
HCR508		346 [13.62]	546 [21.50]	55 [2.17]	200 [7.87]	1,571 CM ³ [95.86 IN ³]	31 KG [68 LBS]
HCR5010		396 [15.59]	646 [25.43]		250 [9.84]	1,963 CM ³ [119.82 IN ³]	34 KG [76 LBS]
HCR5012		446 [17.56]	746 [29.37]		300 [11.81]	2,356 CM ³ [143.78 IN ³]	38 KG [84 LBS]
MAX PRESSURE - 700 BAR/10,150 PSI							

Language Code - Primary/Secondary eng/	Document Type: ID DRAWING	Description: ID SPEC HCR50		
THIRD ANGLE PROJECTION	Technical Reference: Juan Carlos Gomez	Rev A	Date of Issue 2016DEC13	Sheet 1/1
DO NOT SCALE DRAWING	Approver: Steve Held	HCR50ID		
Per ASME Y14.5 - 2009	Creator: John Van Roy	ENERPAC		