



SPECIFICATIONS

	MAX LOAD	DIM "A" COLLAPSED	DIM "A" EXTENDED	STROKE	OIL CAPACITY	WEIGHT
HCR5002	5114 KN/ 575 TON	344 [13.54]	394 [15.51]	50 [1.97]	3,653 CM ³ [222.92 IN ³]	320 KG [706 LBS]
HCR5004		394 [15.51]	494 [19.45]	100 [3.94]	7,306 CM ³ [445.85 IN ³]	361 KG [797 LBS]
HCR5006		444 [17.48]	594 [23.39]	150 [5.91]	10,959 CM ³ [668.77 IN ³]	402 KG [887 LBS]
HCR5008		494 [19.45]	694 [27.32]	200 [7.87]	14,612 CM ³ [891.70 IN ³]	443 KG [977 LBS]
HCR50010		544 [21.42]	794 [31.26]	250 [9.84]	18,265 CM ³ [1114.62 IN ³]	484 KG [1067 LBS]
HCR50012		594 [23.39]	894 [35.20]	300 [11.81]	21,918 CM ³ [1337.55 IN ³]	525 KG [1158 LBS]
MAX PRESSURE - 700 BAR/10,150 PSI						

Language Code - Primary/Secondary eng/	Document Type: ID DRAWING	Description: ID SPEC HCR500			
THIRD ANGLE PROJECTION	Technical Reference: Juan Carlos Gomez	Rev A	Date of Issue 2016DEC13	HCR500ID	Sheet 1/1
DO NOT SCALE DRAWING	Approver: Steve Held				
Per ASME Y14.5 - 2009	Creator: John Van Roy	ENERPAC			