



SPECIFICATIONS

	MAX LOAD	DIM "A" COLLAPSED	DIM "A" EXTENDED	STROKE	OIL CAPACITY	WEIGHT
HCR6002	5987 KN/ 673 TON	352 [13.86]	402 [15.83]	50 [1.97]	4,276 CM ³ [260.97 IN ³]	379 KG [836 LBS]
HCR6004		402 [15.83]	502 [19.76]	100 [3.94]	8,553 CM ³ [521.94 IN ³]	427 KG [940 LBS]
HCR6006		452 [17.80]	602 [23.70]	150 [5.91]	12,829 CM ³ [782.90 IN ³]	474 KG [1044 LBS]
HCR6008		502 [19.76]	702 [27.64]	200 [7.87]	17,106 CM ³ [1043.87 IN ³]	521 KG [1148 LBS]
HCR60010		552 [21.73]	802 [31.57]	250 [9.84]	21,382 CM ³ [1304.84 IN ³]	568 KG [1252 LBS]
HCR60012		602 [23.70]	902 [35.51]	300 [11.81]	25,659 CM ³ [1565.81 IN ³]	615 KG [1356 LBS]

MAX PRESSURE - 700 BAR/10,150 PSI

Language Code - Primary/Secondary eng/	Document Type: ID DRAWING	Description: ID SPEC HCR600		
THIRD ANGLE PROJECTION	Technical Reference: Juan Carlos Gomez	Rev A	Date of Issue 2016DEC13	Sheet 1/1
DO NOT SCALE DRAWING	Approver: Steve Held	HCR600ID		
Per ASME Y14.5 - 2009	Creator: John Van Roy			