



SPECIFICATIONS						
	MAX LOAD	DIM "A" COLLAPSED	DIM "A" EXTENDED	STROKE	OIL CAPACITY	WEIGHT
HCR8002	8149 KN/ 916 TON	404 [15.91]	454 [17.87]	50 [1.97]	5,821 CM <sup>3</sup> [355.21 IN <sup>3</sup> ]	608 KG [1340 LBS]
HCR8004		454 [17.87]	554 [21.81]	100 [3.94]	11,642 CM <sup>3</sup> [710.41 IN <sup>3</sup> ]	674 KG [1485 LBS]
HCR8006		504 [19.84]	654 [25.75]	150 [5.91]	17,462 CM <sup>3</sup> [1065.62 IN <sup>3</sup> ]	740 KG [1631 LBS]
HCR8008		554 [21.81]	754 [29.69]	200 [7.87]	23,283 CM <sup>3</sup> [1420.82 IN <sup>3</sup> ]	806 KG [1777 LBS]
HCR80010		604 [23.78]	854 [33.62]	250 [9.84]	29,104 CM <sup>3</sup> [1776.03 IN <sup>3</sup> ]	872 KG [1922 LBS]
HCR80012		654 [25.75]	954 [37.56]	300 [11.81]	34,925 CM <sup>3</sup> [2131.24 IN <sup>3</sup> ]	938 KG [2068 LBS]
MAX PRESSURE - 700 BAR/10,150 PSI						

Language Code - Primary/Secondary eng/	Document Type: ID DRAWING	Description: ID SPEC HCR800			
<b>THIRD ANGLE PROJECTION</b>	Technical Reference: Juan Carlos Gomez	Rev A	Date of Issue 2016DEC13	HCR800ID	Sheet 1/1
DO NOT SCALE DRAWING	Approver: Steve Held				
Per ASME Y14.5 - 2009	Creator: John Van Roy	<small>This print and information herein is confidential and proprietary and is the property of ENERPAC. It is not to be copied or reproduced without written permission.</small>			