



CAPACITY - 10 TONS [9,07 M.TONS] PUSH
 CAPACITY - 3 TONS [2,72 M.TONS] PULL
 EFFECTIVE AREA - 2.23 SQ.IN. [14,4 SQ.CM.] PUSH
 EFFECTIVE AREA - .75 SQ.IN. [4,8 SQ.CM.] PULL
 INTERNAL PRESSURE AT CAPACITY - 8960 PSI [617,9 BARS] PUSH
 INTERNAL PRESSURE AT CAPACITY - 8000 PSI [551,8 BARS] PULL
 OIL CAPACITY - 22.30 CU.IN [365,0 CU.CM.] PUSH
 OIL CAPACITY - 7.52 CU.IN [123,0 CU.CM.] PULL
 BORE DIA - 1.69 [42,9]
 PLUNGER DIA. - 1.38 [35,1]
 PULL SIDE RELIEF VALVE SET AT - 11,000-11,750 PSI [758,6-810,3]
 WEIGHT - 27.50 LBS. [12.50 Kg.]

15.75 [400,1]
 16.12 [409,5] COLLAPSED HEIGHT
 10.00 [254,0] STROKE
 26.12 [663,5] EXTENDED HEIGHT

EPM57	A	4-1-93	DATE	DIMENSIONS IN BRACKETS ARE IN [mm]		ENERPAC	13000 WEST SILVER SPRING DR. BUTLER, WISCONSIN 53007	
			CHANGES	Specification Sheet				DESCRIPTION
ECO	MODEL NO.	RR1010	DR. R/V	DATE	01/14/93		DRAWING NO.	ID 1683 (A)
			CH. G/B	DATE	4-1-93			

D17114