



CAPACITY - 10 TONS [9,07 M.TONS] PUSH
 CAPACITY - 3 TONS [2,72 M.TONS] PULL
 EFFECTIVE AREA - 2.23 SQ.IN. [14,4 SQ.CM.] PUSH
 EFFECTIVE AREA - .75 SQ.IN. [4,8 SQ.CM.] PULL
 INTERNAL PRESSURE AT CAPACITY - 8960 PSI [617,9 BARS] PUSH
 INTERNAL PRESSURE AT CAPACITY - 8000 PSI [551,8 BARS] PULL
 OIL CAPACITY - 26.76 CU.IN [438,6 CU.CM.] PUSH
 OIL CAPACITY - 8.52 CU.IN [139,6 CU.CM.] PULL
 BORE DIA - 1.69 [42,9]
 PLUNGER DIA. - 1.38 [35,1]
 PULL SIDE RELIEF VALVE SET AT - 11,000-11,750 PSI [758,6-810,3]
 WEIGHT - 29.00 LBS. [13.05 Kg.]

EPM57 A	4-1-93	DATE	DIMENSIONS IN BRACKETS ARE IN [mm]		ENERPAC	13000 WEST SILVER SPRING DR. BUTLER, WISCONSIN 53007	
		CHANGES	Specification Sheet				DESCRIPTION 10 TON CYLINDER
ECD	A	MODEL NO.	RR1012	DR. R/V	DATE 01/14/93	DRAWING NO.	ID 1493 (A)
				CH. GJB	DATE 4-1-93		DWG. SIZE C

D17113