



EFFECTIVE AREA PUSH-70.88 SQ.IN. [457,29 SQ.CM.]
 EFFECTIVE AREA PULL-37.70 SQ.IN. [243,23 SQ.CM.]
 OIL CAP. PUSH-70.88 CU.IN. PER IN. OF STROKE [457,29 CU.CM.]
 OIL CAP. PULL-37.70 CU.IN. PER IN. OF STROKE [243,23 CU.CM.]
 INTERNAL PRESSURE AT CAP. PUSH 9054 P.S.I. [624,4 BAR]
 INTERNAL PRESSURE AT CAP. PULL 10,000 P.S.I. [689,7 BAR]
 FORCE PUSH 600,000 LBS. [272160 KG.]
 FORCE PULL 377,000 LBS. [171007 KG.]
 STROKE 1.00-48.00 IN. [25,40-1219,2 MM]
 BORE Ø9.50 [241,3]

MODEL NO'S RR3001XXXX THRU RR30048XXXX
 SEE CHART BELOW FOR CYLINDER OPTIONS

CYLINDER OPTIONS	SUFFIX LETTERS
COLLAR THREADS	C
PLUNGER THREADS	P
BASE MOUNTING HOLES	B
LIFTING EYES	E

E24200 B 02-22-86/NAK E18821 CHIA MAR 8-14-90	DATE	DIMENSIONS IN BRACKETS ARE IN [mm]	ENERPAC	13000 WEST SILVER SPRING DR. BUTLER, WISCONSIN 53007	
	CHANGES	Specification Sheet			DESCRIPTION 300 TON CYLINDER
ECO	MODEL NO. RR3001 THRU RR30048	DR. M/H	DATE 8-16-90	DRAWING NO. ID1573	D11879
		CH. G/B	DATE 8-28-90		