



EFFECTIVE AREA PUSH-113.10 SQ.IN. [729,7 SQ.CM.]
 EFFECTIVE AREA PULL-62.83 SQ.IN. [405,4 SQ.CM.]
 OIL CAP. PUSH-113.10 CU.IN. PER IN. OF STROKE [1853,4 CU.CM.]
 OIL CAP. PULL-62.83 CU.IN. PER IN. OF STROKE [1029,6 CU.CM.]
 INTERNAL PRESSURE AT CAP. PUSH 8842 P.S.I. [609,8 BAR]
 INTERNAL PRESSURE AT CAP. PULL 10,000 P.S.I. [689,7 BAR]
 FORCE PUSH 1,000,000 LBS. [453600,0 KG.]
 FORCE PULL 628,300 LBS. [284996,9 KG.]
 STROKE 1.00-48.00 IN. [25,4-1219,2 MM]
 BORE Ø12.00 [304,8]
 SADDLE Ø8.00 [203,2]

MODEL NO'S RR5001XXX THRU RR50048XXX SEE CHART BELOW FOR CYLINDER OPTIONS	
CYLINDER OPTIONS	SUFFIX LETTERS
COLLAR THREADS	C
PLUNGER THREADS	P
BASE MOUNTING HOLES	B
LIFTING EYES	E